

**TITLE : NT140WHM-N47****Product Specification****Rev. P0****BOE Optoelectronics Technology Co., Ltd**

SPEC. NUMBER

B82018063

PRODUCT GROUP

TFT-LCD

Rev.

P0

ISSUE DATE

2018.05.22

PAGE

1 OF 34

**REVISION HISTORY** Preliminary Specification Final Specification

Revision No.	Page	Description of Changes	Date	Prepared
P0	-	Initial Release	2018.05.22	Liu Xinghong

**REVIEWED****Designer****Manager**

Wang Xiaolin(Array)

Wang Rui

Wang Dong(Cell)

Hu Jingyong

Pang Jiaqi(CF)

Li Min

Gu Tao(EE)

Xu Bo

Wang Xuefeng(MO)

Li Yucheng

Qin Tian(QE)

Huang Yuan

Wen Jianghong(PI)

Wang Zhihui

**APPROVED**

Liu Xinghong(PM)

## Contents

No.	Items	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	10
5.0	Interface Connection	15
6.0	Signal Timing Specification	20
7.0	Input Signals, Display Colors & Gray Scale of Colors	22
8.0	Power Sequence	23
9.0	Connector Description	24
10.0	Mechanical Characteristics	25
11.0	Reliability Test	26
12.0	Handling & Cautions	26
13.0	Label	27
14.0	Packing Information	29
15.0	Mechanical Outline Dimension	30
16.0	EDID Table	32

## 1.0 GENERAL DESCRIPTION

### 1.1 Introduction

NT140WHM-N47 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 14.0 inch diagonally measured active area with HD resolutions (1366 horizontal by 768 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 262k(6bit) colors and color gamut 45%. The TFT-LCD panel used for this module is a low reflection and higher color type. Therefore, this module is suitable for Notebook PC. The LED driver for back-light driving is built in this model.

All input signals are LVDS interface compatible.




Figure 1. Drive Architecture

### 1.2 Features

- 1 Channel LVDS Interface with 1 pixel / clock
- Thin and light weight
- 262k(6bit) color depth, color gamut 45%
- Single LED lighting bar (Bottom side/Horizontal Direction)
- Data enable signal mode
- Side mounting frame
- Green product (RoHS & Halogen free product)
- On board LED driving circuit
- Low driving voltage and low power consumption
- On board EDID chip

### 1.3 Application

- Notebook PC (Wide type)

### 1.4 General Specification

The followings are general specifications at the model NT140WHM-N47. (listed in Table 1)

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	309.40(H) × 173.95(V)	mm	
Number of pixels	1366 (H) × 768 (V)	pixels	
Pixel pitch	0.2265(H) × 0.2265 (V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	262K		
Color gamut	45%		
Display mode	Normally White		
Dimensional outline	320.4±0.5(H)*205.1±0.5 (V)*3.3(Max)	mm	
Weight	275(max)	g	
Surface treatment	Glare		
Back-light	Bottom edge side, 1-LED lighting bar type		Note 1
Power consumption	P <sub>D</sub> : 0.9	W	@Mosaic
	P <sub>BL</sub> : 2.0	W	
	P <sub>Total</sub> : 2.9	W	@Mosaic

Notes : 1. LED Lighting Bar (27\*LED Array)

## 2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings >

Ta=25+/-2°C

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V <sub>DD</sub>	-0.3	4.0	V	Note 1
Logic Supply Voltage	V <sub>IN</sub>	V <sub>SS</sub> -0.3	V <sub>DD</sub> +0.3	V	
Operating Temperature	T <sub>OP</sub>	0	+50	°C	Note 2
Storage Temperature	T <sub>ST</sub>	-20	+60	°C	

Notes :

1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.

2. Temperature and relative humidity range are shown in the figure below.

95 % RH Max. ( 40 °C ≥ Ta) Maximum wet - bulb temperature at 39 °C or less. (Ta > 40 °C ) No condensation.




Figure 2. Temperature and Relative Humidity Range

## 3.0 ELECTRICAL SPECIFICATIONS

### 3.1 Electrical Specifications

< Table 3. Electrical Specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V <sub>DD</sub>	3.0	3.3	3.6	V	Note 1
Permissible Input Ripple Voltage	V <sub>RF</sub>	-10%*VDD	-	10%*VDD	mV	Note 4
Power Supply Current	I <sub>DD</sub>	-	278	-	mA	Note 1
Power Supply Inrush Current	I <sub>inrush</sub>	-	-	1.5	A	Note 3
Power Consumption	P <sub>D</sub>	-	0.9	-	W	Note 1
	P <sub>BL</sub>	-	-	2.22	W	Note 2
	P <sub>total</sub>	-	-	3.22	W	Note 1

Notes :

1. The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for 3.3V at 25 °C.

a) Typ : Mosaic pattern 8\*8



(a)

Figure 3. Power Measure Patterns

2. Calculated value for reference (V<sub>LED</sub> × I<sub>LED</sub>)

3. Measure condition (Figure 4)

4. Input voltage range:3.0~3.6V.Test condition: Oscilloscope bandwidth 20MHz, AC coupling




Figure 4. Inrush Measure Condition

### 3.2 Backlight Unit

< Table 4. LED Driving Guideline Specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Forward Voltage	V <sub>F</sub>	-	-	2.9	V	
LED Forward Current	I <sub>F</sub>	-	21.6	-	mA	
LED Power Consumption	P <sub>LED</sub>	-	-	2.0	W	Note 1
LED Life-Time	N/A	15,000	-	-	Hour	I <sub>F</sub> = 21.6mA
Power Supply Voltage for LED Driver	V <sub>LED</sub>	5	12	21	V	
Power Supply Voltage for LED Driver Inrush	I <sub>led inrush</sub>	-	-	1.5	A	Note 3
EN Control Level	Backlight On	2	-	5	V	
	Backlight Off	0	-	0.6	V	
PWM Control Level	High Level	2	-	3.6	V	
	Low Level	0	-	0.6	V	
PWM Control Frequency	F <sub>PWM</sub>	200	-	2,000	Hz	
Duty Ratio		5	-	100	%	

Notes :

1. Power supply voltage 12V for LED driver.

Calculator value for reference  $I_F \times V_F \times 27 / \text{driver efficiency} = P_{LED}$

2. The LED life-time define as the estimated time to 50% degradation of initial luminous.

3. Measure condition (Figure 5)




Figure 5. Inrush Measure Condition



### 3.3 LED Structure




Figure 6. LED Structure

## 4.0 OPTICAL SPECIFICATION

### 4.1 Overview

The test of optical specifications shall be measured in a dark room (ambient luminance  $\leq 1$  lux and temperature =  $25 \pm 2^\circ\text{C}$ ) with the equipment of luminance meter system (PR730&PR810) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of  $\theta$  and  $\Phi$  equal to  $0^\circ$ . We refer to  $\theta=0$  ( $=\theta_3$ ) as the 3 o'clock direction (the "right"),  $\theta=90$  ( $=\theta_{12}$ ) as the 12 o'clock direction ("upward"),  $\theta=180$  ( $=\theta_9$ ) as the 9 o'clock direction ("left") and  $\theta=270$  ( $=\theta_6$ ) as the 6 o'clock direction ("bottom"). While scanning  $\theta$  and/or  $\Phi$ , the center of the measuring spot on the display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be  $3.3 \pm 0.3\text{V}$  at  $25^\circ\text{C}$ . Optimum viewing angle direction is 6 o'clock.

### 4.2 Optical Specifications


<Table 5. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle Range	Horizontal	$\theta_3$	CR > 10	-	45	-	Deg.	Note 1
		$\theta_9$		-	45	-	Deg.	
	Vertical	$\theta_{12}$		-	20	-	Deg.	
		$\theta_6$		-	40	-	Deg.	
Luminance Contrast Ratio		CR	$\theta = 0^\circ$	400	500	-		Note 2
Luminance of White	5 Points	$Y_w$	$\theta = 0^\circ$ $I_{LED} = 21.6\text{mA}$	187	220	-	cd/m <sup>2</sup>	Note 3
White Luminance Uniformity	5 Points	$\Delta Y_5$		80	-	-		Note 4
	13 Points	$\Delta Y_{13}$		65	-	-		
White Chromaticity		$W_x$	$\theta = 0^\circ$	0.283	0.313	0.343		Note 5
		$W_y$		0.299	0.329	0.359		
Reproduction of Color	Red	$R_x$	$\theta = 0^\circ$	-0.03	0.578	+0.03		
		$R_y$			0.359			
	Green	$G_x$			0.344			
		$G_y$			0.572			
	Blue	$B_x$			0.161			
		$B_y$			0.129			
Color Gamut				-	45	-	%	
Response Time (Rising + Falling)		$T_{RT}$	$T_a = 25^\circ\text{C}$ $\theta = 0^\circ$	-	12	16	ms	Note 6
Cross Talk		CT	$\theta = 0^\circ$	-	-	2.0	%	Note 7

## Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see Figure 7).
2. Contrast measurements shall be made at viewing angle of  $\Theta = 0$  and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state . (see Figure 7) Luminance Contrast Ratio (CR) is defined mathematically.
 
$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$
3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in Figure 8 for a total of the measurements per display.
4. The White luminance uniformity on LCD surface is then expressed as :  $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points.}$ (see Figure 8 and Figure 9).
5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
6. The electro-optical response time measurements shall be made as Figure 10 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is  $T_r$ , and 90% to 10% is  $T_r$ .
7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark. (See Figure 11).

### 4.3 Optical Measurements



Optical characteristics measurement setup

Figure 7. Measurement Set Up




Figure 8. White Luminance and Uniformity Measurement Locations (5 points)

Center Luminance of white is defined as luminance values of center 5 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in Figure 7 for a total of the measurements per display.




Figure 9. Uniformity Measurement Locations (13 points)

The White luminance uniformity on LCD surface is then expressed as :  $\Delta Y5 = \text{Minimum Luminance of five points} / \text{Maximum Luminance of five points}$  (see Figure 8) ,  $\Delta Y13 = \text{Minimum Luminance of 13 points} / \text{Maximum Luminance of 13 points}$  (see Figure 9).





Figure 10. Response Time Testing

The electro-optical response time measurements shall be made as shown in Figure 10 by switching the “data” input signal ON and OFF. Tr: The luminance to change from 90% to 10% ,Tf: The luminance to change from 10% to 90% .

The test system : PR810



$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Figure 11. Cross Talk Modulation Test Description

Where:

$Y_A$  = Initial luminance of measured area (cd/m<sup>2</sup>)

$Y_B$  = Subsequent luminance of measured area (cd/m<sup>2</sup>)

The location measured will be exactly the same in both patterns

Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance ( $Y_A$ ) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance ( $Y_B$ ) of that same area when any adjacent area is driven dark Refer to Figure 11)

The test system: PR730

## 5.0 INTERFACE CONNECTION

### 5.1 Electrical Interface Connection

The electronics interface connector is STM MSAK24025P40E.

The connector interface pin assignments are listed in Table 6.


<Table 6. Pin Assignments for the Interface Connector>

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	NC	No Connection
2	VDDIN	Power Supply, 3.3V (typ.)
3	VDDIN	Power Supply, 3.3V (typ.)
4	VDC	VDC 3.3Vpower for EDID
5	NC	No Connection
6	CLK EDID	EDID Clock
7	Data EDID	EDID Data
8	RxIN0-	Transmission Data of 0 Negative -
9	RxIN0+	Transmission Data of 0 Positive +
10	GND	Ground
11	RxIN1-	Transmission Data of 1 Negative -
12	RxIN1+	Transmission Data of 1 Positive +
13	GND	Ground
14	RxIN2-	Transmission Data of 2 Negative -
15	RxIN2+	Transmission Data of 2 Positive +
16	GND	Ground
17	RxCLKIN-	Sampling Clock of Negative -
18	RxCLKIN+	Sampling Clock of Positive +
19	NC	No Connection
20	NC	No Connection
21	NC	No Connection
22	GND	Ground
23	NC	No Connection
24	NC	No Connection
25	GND	Ground
26	NC	No Connection
27	NC	No Connection
28	GND	Ground
29	NC	No Connection
30	NC	No Connection

<b>Terminal</b>	<b>Symbol</b>	<b>Functions</b>
Pin No.	Symbol	Description
31	VLED_GND	LED Ground
32	VLED_GND	LED Ground
33	VLED_GND	LED Ground
34	NC	No Connection
35	PWM	System PWM Signal Input
36	LED_EN	LED enable pin(+3.3V Input)
37	NC	No Connection
38	VLED	LED Power Supply 6V-21V
39	VLED	LED Power Supply 6V-21V
40	VLED	LED Power Supply 6V-21V



## 5.2 LVDS Interface



Note. Transmitter : Thine THC63LVDM63A or equivalent.  
 Transmitter is not contained in Module.

## 5.3 Data Input Format




Figure 13. Display Position of Input Data (V-H)

**5.5 Back-light & LCM Interface Connection**

BLU Interface Connector: UJU PF040-B09B-C09.

&lt;Table 7. Pin Assignments for the BLU Connector&gt;

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	LED1	LED cathode connection	6	NC	No Connection
2	LED2	LED cathode connection	7	Vout	LED anode connection
3	LED3	LED cathode connection	8	Vout	LED anode connection
4	NC	No Connection	9	Vout	LED anode connection
5	GND	GND			

## 6.0 SIGNAL TIMING SPECIFICATION

### 6.1 The NT140WHM-N47 Is Operated By The DE Only

< Table 8. Signal Timing Specification >

Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	67.4	72.3	94	MHz
Frame Period		Tv	780	790	900	lines
			-	60	-	Hz
			-	16.7	-	ms
Vertical Display Period		Tvd	-	768	-	lines
One line Scanning Period		Th	1440	1526	1740	clocks
Horizontal Display Period		Thd	-	1366	-	clocks


Note : The above is as optimized setting.

## 6.2 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 9.

<Table 9. LVDS Rx Interface Timing Specification >

Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	-	13.83	25	nsec	
CLK Difference	tCdiff	-tRCIP*(3/7)	0	+tRCIP*(3/7)	nsec	
Input Data 0	tRIP1	-0.4	0.0	+0.4	nsec	
Input Data 1	tRIP0	tRCIP/7-0.4	tRCIP/7	tRCIP/7+0.4	nsec	
Input Data 2	tRIP6	2 × tRCIP/7-0.4	2 × tRCIP/7	2 × tRCIP/7+0.4	nsec	
Input Data 3	tRIP5	3 × tRCIP/7-0.4	3 × tRCIP/7	3 × tRCIP/7+0.4	nsec	
Input Data 4	tRIP4	4 × tRCIP/7-0.4	4 × tRCIP/7	4 × tRCIP/7+0.4	nsec	
Input Data 5	tRIP3	5 × tRCIP/7-0.4	5 × tRCIP/7	5 × tRCIP/7+0.4	nsec	
Input Data 6	tRIP2	6 × tRCIP/7-0.4	6 × tRCIP/7	6 × tRCIP/7+0.4	nsec	



\*  $V_{diff} = (RXO/Ez+) - (RXO/Ez-), \dots, (RXO/ECLK+) - (RXO/ECLK-)$

## 7.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

<Table 10. Input Signal & Basic Display Colors & Gray Scale of Colors >

	Colors & Gray scale	Data signal													
		R0 R1 R2 R3 R4 R5	G0 G1 G2 G3 G4 G5	B0 B1 B2 B3 B4 B5											
Basic colors	Black	0 0 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0											
	Blue	0 0 0 0 0 0	0 0 0 0 0 0	1 1 1 1 1 1											
	Green	0 0 0 0 0 0	1 1 1 1 1 1	0 0 0 0 0 0											
	Light Blue	0 0 0 0 0 0	1 1 1 1 1 1	1 1 1 1 1 1											
	Red	1 1 1 1 1 1	0 0 0 0 0 0	0 0 0 0 0 0											
	Purple	1 1 1 1 1 1	0 0 0 0 0 0	1 1 1 1 1 1											
	Yellow	1 1 1 1 1 1	1 1 1 1 1 1	0 0 0 0 0 0											
	White	1 1 1 1 1 1	1 1 1 1 1 1	1 1 1 1 1 1											
Gray scale of Red	Black	0 0 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0											
	△	1 0 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0											
	Darker	0 1 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0											
	△														
	▽														
	Brighter	1 0 1 1 1 1	0 0 0 0 0 0	0 0 0 0 0 0											
Gray scale of Green	Black	0 0 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0											
	△	0 0 0 0 0 0	1 0 0 0 0 0	0 0 0 0 0 0											
	Darker	0 0 0 0 0 0	0 1 0 0 0 0	0 0 0 0 0 0											
	△														
	▽														
	Brighter	0 0 0 0 0 0	1 0 1 1 1 1	0 0 0 0 0 0											
Gray scale of Blue	Black	0 0 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0											
	△	0 0 0 0 0 0	0 0 0 0 0 0	1 0 0 0 0 0											
	Darker	0 0 0 0 0 0	0 0 0 0 0 0	0 1 0 0 0 0											
	△														
	▽														
	Brighter	0 0 0 0 0 0	0 0 0 0 0 0	1 0 1 1 1 1											
Gray scale of White & Black	Black	0 0 0 0 0 0	0 0 0 0 0 0	0 0 0 0 0 0											
	△	1 0 0 0 0 0	1 0 0 0 0 0	1 0 0 0 0 0											
	Darker	0 1 0 0 0 0	0 1 0 0 0 0	0 1 0 0 0 0											
	△														
	▽														
	Brighter	1 0 1 1 1 1	1 0 1 1 1 1	1 0 1 1 1 1											
White	1 1 1 1 1 1	1 1 1 1 1 1	1 1 1 1 1 1												

## 8.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below.




Figure 15. Power Sequence

- $T1 \leq 10 \text{ ms}$
- $0 \text{ ms} \leq T2 \leq 50 \text{ ms}$
- $200 \text{ ms} \leq T3$
- $10 \text{ ms} \leq T4$
- $10 \text{ ms} \leq T5$
- $0 \text{ ms} \leq T6$
- $10 \text{ ms} \leq T7$
- $200 \text{ ms} \leq T8$
- $0 \text{ ms} \leq T9 \leq 50 \text{ ms}$
- $1 \text{ s} \leq T10$

Notes:

1. When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

## 9.0 Connector Description

Physical interface is described as for the connector on LCM.

These connectors are capable of accommodating the following signals and will be following components.

### 9.1 TFT LCD Module

< Table 11. Signal Connector >

Connector Name /Description	For Signal Connector
Manufacturer	STM
Type/ Part Number	MSAK24025P40E
Mating Housing/ Part Number	I-PEX 20455-040T-11 or Compatible



## 10.0 MECHANICAL CHARACTERISTICS

### 10.1 Dimensional Requirements

Figure 21 shows mechanical outlines for the model NT140WHM-N47 .  
Other parameters are shown in Table 12.

<Table 12. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	309.40(H) × 173.95(V)	mm
Number of pixels	1366 (H) X 768 (V) (1 pixel = R + G + B dots)	pixels
Pixel pitch	0.22629 (H) X 0.22629 (V)	mm
Pixel arrangement	RGB Vertical stripe	
Display colors	262K	
Display mode	Normally white	
Dimensional outline	320.4±0.5(H)×205.1±0.5(V)×3.3(Max)	mm
Weight	275 (max)	g

### 10.2 Mounting

See Figure 21.

### 10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an Anti-Glare coating to minimize reflection and a coating to reduce scratching.

### 10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

## 11.0 RELIABILITY TEST

The reliability test items and its conditions are shown in below.

<Table 13. Reliability Test>

No	Test Items	Conditions
1	High temperature storage test	Ta = 60°C , 60%RH, 240 hrs
2	Low temperature storage test	Ta = -20°C , 240 hrs
3	High temperature & high humidity operation test	Ta = 50°C , 80%RH, 240 hrs
4	High temperature operation test	Ta = 50°C , 60%RH, 240 hrs
5	Low temperature operation test	Ta = 0°C , 240 hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 60% ±3%RH, 100 cycle
7	Vibration test (non-operating)	Ta = 25°C , 60%RH, 1.5G, 10~500Hz, Half Sine X,Y,Z / Sweep rate : 1 hour
8	Shock test (non-operating)	Ta = 25°C , 60%RH, 220G, Half Sine Wave 2msec±X,±Y,±Z Once for each direction
9	Electro-static discharge test (operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV Ta = 25°C , 60%RH,

## 12.0 HANDLING & CAUTIONS

### (1) Cautions when taking out the module

- Pick the pouch only, when taking out module from a shipping package.

### (2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

### (3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

(4) Cautions for the atmosphere

- Dew drop atmosphere should be avoided.
- Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics

- Do not apply fixed pattern data signal to the LCD module at product aging.
- Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions

- Do not disassemble and/or re-assemble LCD module.
- Do not re-adjust variable resistor or switch etc.
- When returning the module for repair or etc. Please pack the module not to be broken. We recommend to use the original shipping packages.

## 13.0 LABEL

(1) Product Label




Figure 17. Product Label

Module ID Naming Rule:

<Table 14. Module ID Naming Rule>

Digit	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
Code	B	9	A	F	1	7	8	8	D	3	8	0	0	0	0	6	8
Description	Product Name		Product Grade	B8	Year		Month	Model Extension Code (Last 4 Digits of FG CODE)				Serial No. 00001-ZZZZZZ					

(2) High voltage caution label




Figure 18. High Voltage Caution Label

(3) Box Label




Figure 19. Box Label

Serial number marked part needs to print, show as follows:

1. FG-CODE(Before 12 bit)
2. Product quantity
3. Box ID
4. Date
5. The client section material number(The client)
6. FG-Code After four
7. The supplier code

Total Size:100×50mm

<Table 15. Box Label Naming Rule >

Digit Code	1	2	3	4	5	6	7	8	9	10	11	12	13
Code	B	9	A	F	1	7	8	N	0	0	3	2	7
Description	Product Name		Product Grade	B8	Year		Month	Revision	BOX Serial Number				

## 14.0 PACKING INFORMATION

### 14.1 Packing Order




Figure 20. Packing Order

### 14.2 Note

- Box dimension: 480mm\*350mm\*285mm
- Package quantity in one box: 35pcs
- Total weight: TBD

## 15.0 MECHANICAL OUTLINE DIMENSION




Figure 21. TFT-LCD Module Outline Dimension (Front View)

Note:

1. PCB side is lower than Top Polarizer.
2. Warps and Deformation are 0.5mm MAX.
3. No light leakage from all 4 corners of LCM.
4. General Tolerance: ±0.3mm.




Figure 23. TFT-LCD Module Outline Dimensions (Rear view)

Note:

1. PCB side is lower than Top Polarizer.
2. Warps and Deformation are 0.5mm MAX.
3. No light leakage from all 4 corners of LCM.
4. General Tolerance:  $\pm 0.3\text{mm}$ .

## 16.0 EDID Table

Address (HEX)	Function	Hex	Dec	Input values.	Notes
00	Header	00	0	0	EDID Header
01		FF	255	255	
02		FF	255	255	
03		FF	255	255	
04		FF	255	255	
05		FF	255	255	
06		FF	255	255	
07		00	0	0	
08	ID Manufacturer Name	09	9	BOE	ID = BOE
09		E5	229		
0A	ID Product Code	E2	226	2018	ID = 2018
0B		07	7		
0C	32-bit serial No.	00	0	0	
0D		00	0	0	
0E		00	0	0	
0F		00	0	0	
10	Week of manufacture	01	1	1	
11	Year of Manufacture	1C	28	2018	Manufactured in 2018
12	EDID Structure Ver.	01	1	1	EDID Ver 1.0
13	EDID revision #	04	4	3	EDID Rev. 0.3
14	Video input definition	95	149	-	digital signal/DP input
15	Max H image size	20	32	32	32 cm (Approx)
16	Max V image size	12	18	19	19 cm (Approx)
17	Display Gamma	78	120	2.2	Gamma curve = 2.2
18	Feature support	02	2	-	RGB display, Preferred Timming mode
19	Red/Green low bits	12	18	-	Red / Green Low Bits
1A	Blue/White low bits	78	112	-	Blue / White Low Bits
1B	Red x high bits	93	147	0.575	Red (x) = 10010011 (0.575)
1C	Red y high bits	5C	92	0.361	Red (y) = 01011100 (0.361)
1D	Green x high bits	56	86	0.336	Green (x) = 01010110 (0.336)
1E	Green y high bits	96	150	0.588	Green (y) = 10010110 (0.588)
1F	Blue x high bits	28	40	0.158	Blue (x) = 00101000 (0.158)
20	Blue y high bits	1B	27	0.105	Blue (y) = 00011011 (0.105)
21	White x high bits	50	80	0.313	White (x) = 01010000 (0.313)
22	White y high bits	54	84	0.329	White (y) = 01010100 (0.329)
23	Established timing 1	00	0	-	
24	Established timing 2	00	0	-	



25	Established timing 3	00	0	-	
26	Standard timing #1	01	1	-	Not Used
27		01	1	-	
28	Standard timing #2	01	1	-	Not Used
29		01	1	-	
2A	Standard timing #3	01	1	-	Not Used
2B		01	1	-	
2C	Standard timing #4	01	1	-	Not Used
2D		01	1	-	
2E	Standard timing #5	01	1	-	Not Used
2F		01	1	-	
30	Standard timing #6	01	1	-	Not Used
31		01	1	-	
32	Standard timing #7	01	1	-	Not Used
33		01	1	-	
34	Standard timing #8	01	1	-	Not Used
35		01	1	-	
36	Detailed timing/monitor descriptor #1	3E	62	72.3	72.3MHz Main clock
37		1C	28		
38		56	86	1366	Hor Active = 1366
39		A0	160	160	Hor Blanking = 160
3A		50	80	-	4 bits of Hor. Active + 4 bits of Hor. Blanking
3B		00	0	768	Ver Active = 1080
3C		16	22	22	Ver Blanking = 22
3D		30	48	-	4 bits of Ver. Active + 4 bits of Ver. Blanking
3E		30	48	48	Hor Sync Offset = 48
3F		20	32	32	H Sync Pulse Width = 32
40		36	54	3	V sync Offset = 3 line
41		00	0	6	V Sync Pulse width : 6 line
42		40	64	320	Horizontal Image Size = 320.4 mm (Low 8 bits)
43		BB	187	187	Vertical Image Size = 187.1 mm (Low 8 bits)
44		10	16	-	4 bits of Hor Image Size + 4 bits of Ver Image Size
45		00	0	0	Hor Border (pixels)
46		00	0	0	Vertical Border (Lines)
47	1A	26		Refer to right table	

48	Detailed timing/monitor descriptor #2	00	0	0	0MHz Main clock
49		00	0		
4A		00	0	0	Hor Active = 0
4B		00	0	0	Hor Blanking = 0
4C		00	0	-	4 bits of Hor. Active + 4 bits of Hor. Blanking
4D		00	0	0	Ver Active = 768
4E		00	0	0	Ver Blanking = 0
4F		00	0	-	4 bits of Ver. Active + 4 bits of Ver. Blanking
50		00	0	0	Hor Sync Offset = 0
51		00	0	0	H Sync Pulse Width = 0
52		00	0	0	V sync Offset = 0 line
53		00	0	0	V Sync Pulse width : 0 line
54		00	0	0	Horizontal Image Size = 0 mm (Low 8 bits)
55		00	0	0	Vertical Image Size = 0 mm (Low 8 bits)
56		00	0	-	4 bits of Hor Image Size + 4 bits of Ver Image Size
57		00	0	0	Hor Border (pixels)
58		00	0	0	Vertical Border (Lines)
59		1A	26	-	
5A		Detailed timing/monitor descriptor #3	00	0	-
5B	00		0	-	
5C	00		0	-	Reserved
5D	FE		254	-	Tag : ASCII String
5E	00		0		Reserved
5F	42		66	B	Manufacture name : BOECQ
60	4F		79	O	
61	45		69	E	
62	20		32		
63	43		67	C	
64	51		81	Q	
65	0A		10		
66	20		32		
67	20	32			
68	20	32			
69	20	32			
6A	20	32			
6B	20	32			

6C	Detailed timing/monitor descriptor #4	00	0	-	Indicates descriptor #4 is a display Descriptor
6D		00	0	-	
6E		00	0	-	
6F		FE	254	-	Tag : ASCII String
70		00	0	-	Reserved
71		4E	78	N	Model name : NT140WHM-N47
72		54	84	T	
73		31	49	1	
74		34	52	4	
75		30	48	0	
76		57	87	W	
77		48	72	H	
78		4D	77	M	
79		2D	45	-	
7A		4E	78	N	
7B		34	52	4	
7C		37	55	7	
7D		0A	10	-	
7E		Extension flag	00	0	1
7F	Checksum	6B	107	-	